Section V - HEALTH HAZARD DATA

See Section II THRESHOLD LIMIT VALUE :

Headache, nausea, dizziness. Breathing vapor will be EFFECTS OF OVEREXPOSURE:

irritating to nose, throat and eyes.

EMERGENCY AND FIRST AID PROCEDURES: Skin Exposure: Wash affected area with soap & water.

Eye Exposure: Flush with water for at least 15 minutes, consult physician.

Ingestion: Consult physician immediately.

Inhalation: Remove victim to fresh air, consult physician.

Section VI -	REAC	TIVITY [ATAC
--------------	------	----------	------

STARILITY UNSTABLE XX STABLE conditions to Avoid: Storage at high temperatures. INCOMPATABILITY (Materials to avoid) Strong oxidizing agents. Sparks and open flame. HAZARDOUS DECOMPOSITION PRODUCTS

On combustion CO, CO2, Aldehydes and other organics, lead fumes, oxides of nitrogen.

HAZARDOUS POLYMERIZATION

MAY OCCUR XX WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate sources of ignition and clear fumes from area. Prevent liquid from entering sewers, water sources, or low areas. Keep unnecessary personnel away. Shut off source, if possible to do so without hazard. Contain spilled liquid with sawdust, sand or oil absorbing compound. wastedsposal METHOD Wash area with detergent & water. Consult disposal expert & ensure conformity with local regulations.

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Use approved respiratory protection such as an air-supplied mask if used in non ventilated area.

Mechanical: Explosion-proof ventilation equipment. No smoking or open lights.

VENTILATION: Face velosity 60 fpm in confined area.

PROTECTIVE GLOVES: Chemically resistant gloves.

EYE PROTECTION: Chemical splash goggles or face shield.

OTHER PROTECTIVE EQUIPMENT: Eye bath & safety shower.

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers closed when not in use. handle or store near flame, heat or strong oxidants. Adequate ventilation required. Containers of this product may be hazardous when emptied -these OTHER PRECAUTIONS CONTAINERS retain product residues (vapor, liquid, etc.).

All handling equipment should be electrically grounded. Treat as a very flammable liquid.

Technical Administrativé Manager